

# YD-A Spinner Info

May 2010

<u>ENGINE SIZE &amp; TYPE</u>	<u>THREAD SIZE</u>	<u>STEP</u>	<u>BUSHING REQUIRED</u>
23cc Single Gas The Prop Shaft is a threaded stud with removable 8x1.25mm threaded Nut.(It is not tapped.)	8x1.25mm	NO	No
28cc JC-EVO Gas Single The Prop Shaft is a threaded stud with removable 8x1.25mm threaded Nut with a 10mm step. (It is not tapped.)	8x1.25mm	YES	Ream 10mm
32cc Single Gas The Prop Shaft is a threaded stud with removable 8x1.25mm threaded Nut.(It is not tapped.)	8x1.25mm	NO	No
38cc Single Gas The Prop Shaft is a threaded stud with removable 10x1.25mm threaded Nut.(It is not tapped.)	10x1.25mm	NO	No
42cc Single Gas The Prop Shaft is a threaded stud with removable 10x1.25mm threaded Nut.(It is not tapped.)	10x1.25mm	NO	No

<u>ENGINE SIZE &amp; TYPE</u>	<u>THREAD SIZE</u>	<u>STEP</u>	<u>BUSHING REQUIRED</u>
56cc Gas Drill .205 Dia. 4 @ 90 Deg. on a 30mm Bolt Circle (Exact Same as DA-50)	4 Bolt 5mm	NO	Ream 10mm

<u>ENGINE SIZE &amp; TYPE</u>	<u>THREAD SIZE</u>	<u>STEP</u>	<u>BUSHING REQUIRED</u>
64cc Twin The Prop Shaft is a threaded stud with removable 10x1.25mm threaded Nut.(It is not tapped.)	10x1.25mm	NO	(NO Adapter)
76cc Twin The Prop Shaft is a threaded stud with removable 10x1.25mm threaded Nut.(It is not tapped.)	10x1.25mm	NO	
84cc Twin The Prop Shaft is a threaded stud with removable 10x1.25mm threaded Nut.(It is not tapped.)	10x1.25mm	NO	
112cc Single (Confirmed) Six Bolt Drive Hub with 10mm pilot Shaft (Like 3W) (Not same Bolt Circle) Drill .205 Dia. Holes, 6 @ 60 Deg., On 30mm Bolt Circle & Ream Center Hole 10mm	6 Bolt	NO	Ream 10mm

Company or Mfg. Name and Contact:  
 RC Aero Products LLC Henry Zwolak  
 Tel: 1-888-239-8593  
[www.rcaer.com](http://www.rcaer.com)