


TECHNICAL DATA

Nominal voltage: 600V

Testing Voltage: 2000V

Temperature Rang : -60°C- +200°C Conductor: Tinned copper

OD tolerance: ±0.1MM Insulator: Silicone



导体/conductor			绝缘体/Insulator		电气特性 Electrical Characteris tic	截面 面积	允载电流 Permissi ble ampacity 20°C-AMR	包装规格 Packing
线号 AWG	导体构造 Construction No. x φ mm	直径 Diameter (mm)	绝缘厚度 Insulator Thick (mm)	完成外径 Over Diameter (mm)	导体电阻 Realst. max Cuc, c20°C (ohm/km)	(毫米* 毫米)	安培 (A)	米/卷 Mt/coils
30	20/0.06 11/0.08	0.30	0.55	1.20	331.00	0.05	0.80	100
28	28/0.06 16/0.08	0.36	0.55	1.30	227.20	0.08	1.25	100
26	42/0.06 30/0.08	0.46	0.55	1.50	123.00	0.14	3.50	100
24	70/0.06 40/0.08	0.61	0.55	1.60	97.60	0.20	5.00	100
22	110/0.06 60/0.08	0.78	0.55	1.70	88.60	0.33	8.73	100
20	180/0.06 100/0.08	0.92	0.55	1.80	62.50	0.50	13.87	100
18	270/0.06 150/0.08	1.19	0.55	2.30	39.50	0.75	22.00	100
16	455/0.06 252/0.08	1.53	0.8	3.00	24.40	1.27	35.00	100
15	856/0.05 336/0.08	1.69	0.8	3.10	20.02	1.68	42.00	100
14	720/0.06 400/0.08	1.78	0.9	3.50	15.60	2.07	55.60	100
13	1296/0.05 500/0.08	2.06	0.95	4.00	12.50	2.50	65.00	100
12	1100/0.06 680/0.08	2.48	1.00	4.50	9.80	3.40	88.40	100
11	1171/0.05 788/0.08	2.59	1.00	4.60	7.38	3.96	100.0	100
10	1780/0.06 1050/0.08	3.06	1.00	5.50	6.30	5.30	140.6	100
8	2933/0.06 1650/0.08	3.75	1.50	6.80	4.20	8.29	200	100